CE Marked

## Ultra-Lok® Tie

| Part No. | Material* | Width In | Width mm | Length In | Length mm | Thickness In | Thickness mm | Maximum Diameter Single Wrap In | Maximum Diameter Single Wrap mm | Minimum Loop Tensile Strength (Lbs) | Package Quantity | Package Weight Lbs | Package Weight Kg | Application Tools |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| AU2029 | 201 SS | 1/4 | 6.4 | 8 | 203 | 0.015 | 0.38 | 1.5 | 38 | 400 | 100/bag | 1.0 | 0.5 | A94079 IT3000 |
| AU2039 | 201 SS | 1/4 | 6.4 | 10 | 254 | 0.015 | 0.38 | 2.5 | 63 | 400 | 100/bag | 1.2 | 0.6 | |
| AU2049 | 201 SS | 1/4 | 6.4 | 12 | 305 | 0.015 | 0.38 | 3.0 | 76 | 400 | 100/bag | 1.4 | 0.7 | |
| AU2059 | 201 SS | 1/4 | 6.4 | 14 | 356 | 0.015 | 0.38 | 3.8 | 96 | 400 | 100/bag | 1.6 | 0.8 | |
| AU2069 | 201 SS | 1/4 | 6.4 | 16 | 406 | 0.015 | 0.38 | 4.5 | 114 | 400 | 100/bag | 1.9 | 0.9 | |
| AU2079 | 201 SS | 1/4 | 6.4 | 19 | 483 | 0.015 | 0.38 | 5.4 | 137 | 400 | 100/bag | 2.2 | 1.0 | |
| AU2089 | 201 SS | 1/4 | 6.4 | 24 | 610 | 0.015 | 0.38 | 7.0 | 177 | 400 | 100/bag | 2.7 | 1.3 | |
| AU2099 | 201 SS | 1/4 | 6.4 | 29 | 737 | 0.015 | 0.38 | 8.0 | 215 | 400 | 100/bag | 3.3 | 1.5 | |
| AU2159 | 201 SS | 1/4 | 6.4 | 35 | 889 | 0.015 | 0.38 | 10.5 | 266 | 400 | 100/bag | 3.9 | 1.8 | |




**A94079 Ultra-Lok® Tool**
Adjustable tension, forms lock, cuts off tail.



**Ultra-Lok® Tie**

CE Marked, DNV Approved, Coast Guard Approved

## Ball-Lok Tie

| Part No. Uncoated | Part No. Coated | Material* | Width In | Width mm | Length In | Length mm | Base Material Thickness In | Base Material Thickness mm | Maximum Diameter Single Wrap In | Maximum Diameter Single Wrap mm | Minimum Loop Tensile Strength (Lbs) | Package Quantity | Package Weight Lbs | Package Weight Kg | Application Tools |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| KE1128 | - | 304 SS | 0.180 | 4.6 | 7.9 | 201 | 0.010 | 0.25 | 2.0 | 50 | 200 | 100/bag | 0.6 | 0.3 | K50289 or by hand |
| KE1138 | - | 304 SS | 0.180 | 4.6 | 10.2 | 259 | 0.010 | 0.25 | 2.7 | 69 | 200 | 100/bag | 0.7 | 0.4 | |
| KE1148 | - | 304 SS | 0.180 | 4.6 | 14.2 | 360 | 0.010 | 0.25 | 4.0 | 102 | 200 | 100/bag | 0.9 | 0.5 | |
| KE1158 | - | 304 SS | 0.180 | 4.6 | 20.4 | 520 | 0.010 | 0.25 | 6.0 | 152 | 200 | 100/bag | 1.3 | 0.6 | |
| KE1168 | - | 304 SS | 0.180 | 4.6 | 26.8 | 679 | 0.010 | 0.25 | 8.0 | 203 | 200 | 100/bag | 1.8 | 0.8 | |
| KE1178 | - | 304 SS | 0.180 | 4.6 | 33.0 | 838 | 0.010 | 0.25 | 10.0 | 254 | 200 | 100/bag | 2.1 | 1.0 | |
| KE1188 | - | 304 SS | 0.180 | 4.6 | 42.0 | 1067 | 0.010 | 0.25 | 12.0 | 305 | 200 | 100/bag | 2.4 | 1.1 | |
| KE0128 | - | 316 SS | 0.180 | 4.6 | 7.9 | 201 | 0.010 | 0.25 | 2.0 | 50 | 200 | 100/bag | 0.6 | 0.3 | |
| KE0138 | - | 316 SS | 0.180 | 4.6 | 10.2 | 259 | 0.010 | 0.25 | 2.7 | 69 | 200 | 100/bag | 0.7 | 0.4 | |
| KE0148 | - | 316 SS | 0.180 | 4.6 | 14.2 | 360 | 0.010 | 0.25 | 4.0 | 102 | 200 | 100/bag | 0.9 | 0.5 | |
| KE0158 | - | 316 SS | 0.180 | 4.6 | 20.4 | 520 | 0.010 | 0.25 | 6.0 | 152 | 200 | 100/bag | 1.3 | 0.6 | |
| KE0168 | - | 316 SS | 0.180 | 4.6 | 26.8 | 679 | 0.010 | 0.25 | 8.0 | 203 | 200 | 100/bag | 1.8 | 0.8 | |
| KE0178 | - | 316 SS | 0.180 | 4.6 | 33.0 | 838 | 0.010 | 0.25 | 10.0 | 254 | 200 | 100/bag | 2.1 | 1.0 | |
| KE0188 | - | 316 SS | 0.180 | 4.6 | 42.0 | 1067 | 0.010 | 0.25 | 12.0 | 305 | 200 | 100/bag | 2.4 | 1.1 | |
| KE1328 | - | 304 SS | 0.310 | 7.9 | 7.9 | 201 | 0.010 | 0.25 | 2.0 | 50 | 300 | 100/bag | 1.0 | 0.5 | |
| KE1338 | - | 304 SS | 0.310 | 7.9 | 10.2 | 259 | 0.010 | 0.25 | 2.7 | 69 | 300 | 100/bag | 1.3 | 0.6 | |
| KE1348 | - | 304 SS | 0.310 | 7.9 | 14.2 | 360 | 0.010 | 0.25 | 4.0 | 102 | 300 | 100/bag | 1.7 | 0.8 | |
| KE1358 | - | 304 SS | 0.310 | 7.9 | 20.4 | 520 | 0.010 | 0.25 | 6.0 | 152 | 300 | 100/bag | 2.2 | 1.1 | |
| KE1368 | - | 304 SS | 0.310 | 7.9 | 26.8 | 679 | 0.010 | 0.25 | 8.0 | 203 | 300 | 100/bag | 2.9 | 1.3 | |
| KE1378 | - | 304 SS | 0.310 | 7.9 | 33.0 | 838 | 0.010 | 0.25 | 10.0 | 254 | 300 | 100/bag | 3.5 | 1.6 | |
| KE1388 | - | 304 SS | 0.310 | 7.9 | 42.0 | 1067 | 0.010 | 0.25 | 12.0 | 305 | 300 | 100/bag | 4.6 | 2.1 | |
| KE0328 | - | 316 SS | 0.310 | 7.9 | 7.9 | 201 | 0.010 | 0.25 | 2.0 | 50 | 300 | 100/bag | 1.0 | 0.5 | |
| KE0338 | - | 316 SS | 0.310 | 7.9 | 10.2 | 259 | 0.010 | 0.25 | 2.7 | 69 | 300 | 100/bag | 1.3 | 0.6 | |
| KE0348 | - | 316 SS | 0.310 | 7.9 | 14.2 | 360 | 0.010 | 0.25 | 4.0 | 102 | 300 | 100/bag | 1.7 | 0.8 | |
| KE0358 | - | 316 SS | 0.310 | 7.9 | 20.4 | 520 | 0.010 | 0.25 | 6.0 | 152 | 300 | 100/bag | 2.2 | 1.1 | |
| KE0368 | - | 316 SS | 0.310 | 7.9 | 26.8 | 679 | 0.010 | 0.25 | 8.0 | 203 | 300 | 100/bag | 2.9 | 1.3 | |
| KE0378 | - | 316 SS | 0.310 | 7.9 | 33.0 | 838 | 0.010 | 0.25 | 10.0 | 254 | 300 | 100/bag | 3.5 | 1.6 | |
| KE0388 | - | 316 SS | 0.310 | 7.9 | 42.0 | 1067 | 0.010 | 0.25 | 12.0 | 305 | 300 | 100/bag | 4.6 | 2.1 | |
| - | KE0828 | 316 SS | 0.310 | 7.9 | 7.9 | 201 | 0.010 | 0.25 | 2.0 | 50 | 300 | 100/bag | 1.2 | 0.6 | |
| - | KE0848 | 316 SS | 0.310 | 7.9 | 14.2 | 360 | 0.010 | 0.25 | 4.0 | 102 | 300 | 100/bag | 1.8 | 0.9 | |
| - | KE0858 | 316 SS | 0.310 | 7.9 | 20.4 | 520 | 0.010 | 0.25 | 6.0 | 152 | 300 | 100/bag | 2.5 | 1.2 | |




**K50289 Ball-Lok Tool**
Adjustable tension, forms lock, cuts off tail.




**Ball-Lok Ties**



**AE2009 Cable Tie Tensioner**

UL listed, CE Marked, DNV Approved

## Multi-Lok Tie

| Part No. Uncoated | Part No. Coated | Material* | Width In | Width mm | Length In | Length mm | Thickness Uncoated In | Thickness Uncoated mm | Thickness Coated In | Thickness Coated mm | Maximum Diameter Single Wrap In | Maximum Diameter Single Wrap mm | Minimum Loop Tensile Strength (Lbs) | Package Quantity | Package Weight Lbs | Package Weight Kg | Application Tools |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| AE6019 | AE6119 | 316 SS | 0.270 | 6.9 | 6.0 | 150 | 0.011 | 0.28 | 0.018 | 0.46 | 1.3 | 33 | 250 | 100/bag | 0.7 | 0.3 | AE2009 AE2018 M50389 or by hand |
| AE6029 | AE6129 | 316 SS | 0.270 | 6.9 | 9.0 | 225 | 0.011 | 0.28 | 0.018 | 0.46 | 2.2 | 57 | 250 | 100/bag | 0.9 | 0.5 | |
| AE6039 | AE6139 | 316 SS | 0.270 | 6.9 | 12.0 | 300 | 0.011 | 0.28 | 0.018 | 0.46 | 3.2 | 81 | 250 | 100/bag | 1.3 | 0.6 | |
| AE6049 | AE6149 | 316 SS | 0.270 | 6.9 | 18.0 | 450 | 0.011 | 0.28 | 0.018 | 0.46 | 5.1 | 129 | 250 | 100/bag | 1.8 | 0.8 | |
| AE6059 | AE6159 | 316 SS | 0.270 | 6.9 | 24.0 | 610 | 0.011 | 0.28 | 0.018 | 0.46 | 7.1 | 180 | 250 | 100/bag | 2.6 | 1.2 | |
| AE7019 | AE7119 | 316 SS | 0.470 | 11.9 | 6.0 | 150 | 0.011 | 0.28 | 0.018 | 0.46 | 1.3 | 33 | 400 | 100/bag | 1.1 | 0.5 | |
| AE7029 | AE7129 | 316 SS | 0.470 | 11.9 | 9.0 | 225 | 0.011 | 0.28 | 0.018 | 0.46 | 2.2 | 57 | 400 | 100/bag | 1.7 | 0.8 | |
| AE7039 | AE7139 | 316 SS | 0.470 | 11.9 | 12.0 | 300 | 0.011 | 0.28 | 0.018 | 0.46 | 3.2 | 81 | 400 | 100/bag | 2.2 | 1.0 | |
| AE7049 | AE7149 | 316 SS | 0.470 | 11.9 | 18.0 | 450 | 0.011 | 0.28 | 0.018 | 0.46 | 5.1 | 129 | 400 | 100/bag | 3.0 | 1.4 | |
| AE7059 | AE7159 | 316 SS | 0.470 | 11.9 | 24.0 | 610 | 0.011 | 0.28 | 0.018 | 0.46 | 7.1 | 180 | 400 | 100/bag | 4.3 | 2.0 | |



**M50389 Multi-Lok Hand Tool**
Adjustable tension, forms lock, cuts off tail.



**Multi-Lok Ties**

*BAND-IT reserves the right to substitute material with equal or better corrosion resistance and/or mechanical specifications.



Printed on recycled paper