

# Band-It BAND-FAST - Cable Cleat Alternative

| PPA Coated BAND-FAST® Clamps |           |           |          |           |                       |                                     |                                      |   |              |  |
|------------------------------|-----------|-----------|----------|-----------|-----------------------|-------------------------------------|--------------------------------------|---|--------------|--|
| Item Code                    | Band Code | Clip Code | Width mm | Length mm | Single or Double Wrap | Max Cable OD Single Cable Config mm | Max Cable OD Trefoil Cable Config mm | Max Cable OD Quadrafoil Cable Config mm | Qty per Pack | Passed IEC61914:2015 Short Circuit Test in Trefoil up to (kA Peak) |
| CFAC-F1015M030-A900          | AE435     | AE455     | 15.88    | 300       | Single                | 40                                  | 13                                   | 12                                      | 100          | 50.8kA   |
| CFAC-F1015M040-A900          | AE435     | AE455     | 15.88    | 400       | Single                | 75                                  | 28                                   | 25                                      | 100          | 50.8kA   |
| CFAC-F1015M050-A900          | AE435     | AE455     | 15.88    | 500       | Single                | 100                                 | 43                                   | 37                                      | 100          | 50.8kA   |
| CFAC-F1015M060-A900          | AE435     | AE455     | 15.88    | 600       | Single                | 130                                 | 57                                   | 50                                      | 100          | 50.8kA   |
| CFAC-F1015M070-A900          | AE435     | AE455     | 15.88    | 700       | Single                | 160                                 | 70                                   | 60                                      | 100          | 50.8kA   |
| CFFC-F1015M030-A900          | AE435     | LE155     | 15.88    | 300       | Double                | 25                                  | 10                                   | 9                                       | 100          | 76.3kA   |
| CFFC-F1015M040-A900          | AE435     | LE155     | 15.88    | 400       | Double                | 40                                  | 13                                   | 12                                      | 100          | 76.3kA   |
| CFFC-F1015M050-A900          | AE435     | LE155     | 15.88    | 500       | Double                | 55                                  | 21                                   | 18                                      | 100          | 76.3kA   |
| CFFC-F1015M060-A900          | AE435     | LE155     | 15.88    | 600       | Double                | 70                                  | 28                                   | 25                                      | 100          | 76.3kA   |
| CFFC-F1015M070-A900          | AE435     | LE155     | 15.88    | 700       | Double                | 85                                  | 35                                   | 31                                      | 100          | 76.3kA   |
| CFFC-F1015M080-A900          | AE435     | LE155     | 15.88    | 800       | Double                | 100                                 | 42                                   | 37                                      | 100          | 76.3kA   |
| CFFC-F1015M100-A900          | AE435     | LE155     | 15.88    | 1000      | Double                | 130                                 | 57                                   | 50                                      | 100          | 76.3kA   |
| CFFC-F1015M120-A900          | AE435     | LE155     | 15.88    | 1200      | Double                | 160                                 | 70                                   | 60                                      | 100          | 76.3kA   |

| Uncoated BAND-FAST® with Ear-Lokt Buckle |           |             |          |           |                       |                                     |                                      |   |              |  |
|--|-----------|-------------|----------|-----------|-----------------------|-------------------------------------|--------------------------------------|---|--------------|--|
| Item Code                                | Band Code | Buckle Code | Width mm | Length mm | Single or Double Wrap | Max Cable OD Single Cable Config mm | Max Cable OD Trefoil Cable Config mm | Max Cable OD Quadrafoil Cable Config mm | Qty per Pack | Passed IEC61914:2015 Short Circuit Test in Trefoil up to (kA Peak) |
| CFEC-F1030M050                           | C405      | C455        | 15.88    | 500       | Double                | 55                                  | 21                                   | 18                                      | 100          | 112kA  |
| CFEC-F1030M060                           | C405      | C455        | 15.88    | 600       | Double                | 70                                  | 28                                   | 25                                      | 100          | 112kA  |
| CFEC-F1030M070                           | C405      | C455        | 15.88    | 700       | Double                | 85                                  | 35                                   | 31                                      | 100          | 112kA  |
| CFEC-F1030M080                           | C405      | C455        | 15.88    | 800       | Double                | 100                                 | 42                                   | 37                                      | 100          | 112kA  |
| CFEC-F1030M100                           | C405      | C455        | 15.88    | 1000      | Double                | 130                                 | 57                                   | 50                                      | 100          | 112kA  |
| CFEC-F1030M120                           | C405      | C455        | 15.88    | 1200      | Double                | 160                                 | 70                                   | 60                                      | 100          | 112kA  |
| CFEC-F1230M050                           | C406      | C456        | 19.05    | 500       | Double                | 55                                  | 21                                   | 18                                      | 100          | 120kA  |
| CFEC-F1230M060                           | C406      | C456        | 19.05    | 600       | Double                | 70                                  | 28                                   | 25                                      | 100          | 120kA  |
| CFEC-F1230M070                           | C406      | C456        | 19.05    | 700       | Double                | 85                                  | 35                                   | 31                                      | 100          | 120kA  |
| CFEC-F1230M080                           | C406      | C456        | 19.05    | 800       | Double                | 100                                 | 42                                   | 37                                      | 100          | 120kA  |
| CFEC-F1230M100                           | C406      | C456        | 19.05    | 1000      | Double                | 130                                 | 57                                   | 50                                      | 100          | 120kA  |
| CFEC-F1230M120                           | C406      | C456        | 19.05    | 1200      | Double                | 160                                 | 70                                   | 60                                      | 100          | 120kA  |

PPA Coated BAND-FAST™ Clamps with clips have 0.38mm 316SS band thickness (1.2mm thick with coating) Use **C075 Tool Only**

Uncoated BAND-FAST™ Clamps with Ear-Lokt Buckles have 0.76mm 316SS band thickness Use **C001 Tool Only**

Uncoated BAND-FAST™ Clamps with Ear-Lokt Buckles should be installed with additional polymeric channel to ensure maximum results



|                  |                  |
|------------------|------------------|
| <b>C075 Tool</b> | <b>C001 Tool</b> |
|------------------|------------------|